White Paper: Integrated Rapid Response Containment (IRRC) System

Concept by: Bernard Bedard

Project Focus: On-Site 3D-Extrusion of Marine Oil Barriers

1. Executive Summary

The IRRC system is a "vessel-as-a-factory" model designed to solve the logistical failures of traditional oil spill response. By using **mechanical frothing** to extrude a high-buoyancy, 12-inch "puffy" silicone log over a structural wire-rope core, the system enables zero-hour containment directly from the source vessel. This system prioritizes **minimal storage footprint**, **site-specific density control**, and a **closed-loop recovery process**.

2. The Problem: The "Deployment Gap"

Current oil spill technologies suffer from three critical failures identified during the *Exxon Valdez* disaster:

- **Logistical Lag:** Traditional booms are bulky and stored at distant ports, leading to hours or days of spread before containment begins.
- **Storage Constraints:** Modern tankers lack the deck space to carry miles of pre-inflated or foam-filled booms.
- **Waste Volume:** Oily, spent absorbent booms create massive amounts of hazardous waste that are difficult to manage at sea.

3. The Solution: "Whipped" Silicone Extrusion

The IRRC system replaces physical stockpiles with liquid precursors.

- **The Chemistry:** A proprietary two-part, platinum-catalyzed silicone designed for a "snap-set" (solidification) in under 60 seconds.
- **The "Whip":** High-speed mechanical agitation and compressed air create a "puffy," closed-cell foam log. This 12-inch diameter barrier uses an 8:1 expansion ratio to maximize volume while minimizing chemical costs.
- **The Skeleton:** A central **stainless steel wire rope** is encapsulated during extrusion, providing the tensile strength necessary for high-tension towing and mechanical retrieval.

4. Structural Support: The "Floating Tail"

To ensure the silicone cures perfectly before hitting the water, the system utilizes a **Dynamic Floating Support** ramp:

- **Segmented Buoyancy:** A series of articulated, V-shaped floating pods trail behind the catamaran.
- **Surface-Following:** These pods cradle the 12-inch log, shielding the "wet" silicone from wave impact during the 30-second skin-over phase.
- **Automated Recovery:** As the boat moves, the pods are pulled back into the hull tunnel and stacked vertically to save space.

5. The Responder Catamaran & Smart Tether

The system is housed on an independent, dual-hull vessel for maximum stability.

- **Smart Tether:** An umbilical link to the mother ship provides 24/7 **Automated Maintenance**, regulating chemical temperatures and performing self-diagnostic checks to ensure 100% "Ready-State."
- **Pilot-Initiated Launch:** A "Hot Start" command allows the pilot to launch the catamaran and begin "printing" a 360-degree containment circle (the "Lasso") in under 60 seconds.

6. Closed-Loop Recovery & "Squeegee" Processing

Retrieval is handled via a mechanical interface at the stern:

- **Squeegee Rollers:** Dual-pressure rollers compress the non-absorbent log, "wringing" the surface oil into collection bladders.
- **Stripping Die:** A calibrated circular die peels the "spent" silicone skin off the wire rope.
- **Shredder:** The dry silicone is shredded into compact, inert chips for easy disposal, while the **clean wire rope** is re-spooled for immediate reuse.

7. Conclusion

The IRRC system moves the industry from **passive storage** to **active manufacturing**. By tuning density to maintain a specific submerged draft, the system prevents oil from "entraining" under the barrier. It is a cost-effective, site-specific, and zero-waste solution for modern maritime environmental protection.